





because it works

# INJECT 2K 230030

## SCOPE OF DELIVERY

2K high pressure dosing pump in galvanized steel or stainless steel, maintenance unit, chassis or rack, 2x pressure gauges at the material outlet, relief for A & B components, operating instructions (the stainless steel version includes a Profit rinsing pump)

TECHNICAL DATA	Inject 2K 230030 F	Inject 2K 230030 GS
Output per double stroke	194 ccm	194 ccm
Pressure ratio	30:1	30:1
Max. air inlet pressure	8 bar	8 bar
Max. operating pressure	240 bar	240 bar
Mixing ratio	1:1	1:1
Flush pump	27.33	27.33
Air connection	G 1" inner thread	G 1" inner thread
Order number galvanized steel	0669708	0669709
Order number stainless steel	0669711	0669712
Order number galvanized steel complete device with ASL, hose package and mixing unit	0669992	on enquiry
Order number stainless steel complete device with ASL, hose package and mixing unit	0669993	on enquiry

EQUIPMENT	Description	Order Number
Suction	Suction hose small container and 200 l	0669820
	Suction hose IBC RS	0669595
	Mounting kit frame 68 l plastic barrel	0670111
Flush pump	Profit	0669718
Equipment	Grid for frame	0669630
Evaluation unit	Stroke counter	0646640
	Inject Guard	0669642 + 0669489
Hose package	NW10 - (3/8") RS with flush hose	0669613
	NW10 - (3/8") RS with flush hose for Inject Guard (230er)	0669663
	NW10 - (3/8") RS without flush hose	0669766
Mixing unit	Standard 2K 3/8" RS with flush hose	0669611
	Inject Guard with flush hose 3/8" RS	0669600

<b>i</b>	<b>N = Normal steel galvanized, not rustproof</b>	<b>RS = Stainless steel, rust and acid resistant</b>
	<b>F = Chassis</b>	<b>GS = Rack</b>